

JET 520



M1 / BS

• APPLICATIONS

Frontlit

- One side printing
- Digital printing: solvent / eco-solvent and UV inks
- Screenprinting: solvent and UV inks

- Indoor / Outdoor
Banners / signage / POS / wall covering / indoor communication

• PRODUCT INFORMATION

Super wide format: 3.20m
Rolls of: 60 and 250 lm / printable side inside

Wide format: 1.37m / 1.62m / 3.20m
Rolls of: 30 lm / printable side outside

Screenprinting: 3.20m
Rolls of: 60 and 250 lm / printable side inside

- Weight 550 g/m²
- Base cloth high tenacity polyester 1100 Dtex
- Coating PVC coating, system LOWICK
- Finish satin inkjet lacquer one side
- Colour white 7325

• PRODUCT CHARACTERISTICS

- | | | |
|-------------------------|-----------------------|---------------------|
| - Tensile strength | 200/210 daN | NF EN ISO 1421 |
| - Tear strength | 30/20 daN | DIN 53363 |
| - Adhesion | 7 daN/5 cm | NF EN ISO2411 |
| - Translucency | 5 % | XP T 54 199 |
| - Thickness | 0.44 mm | |
| - Temperature stability | | |
| in Celsius | - 30 °C to +70 °C | |
| in Fahrenheit | - 22 °F to +158 ° | |
| - F/R | M1 | PV N ° LYC 064240 L |
| | BS - C12 | |
| | NFPA 701 - MEA - CSFM | |

Average values +/- 10% non contractual

Collection 2009
Edition 01/2009

