

# JET 520

Frontlit



M1/B1/BS/CI2

•APPLICATIONS

- One side printing
- Digital printing: solvent / eco-solvent and UV inks
- Screenprinting: solvent and UV inks

- Indoor / Outdoor

Banners / signage / POS / wall covering / indoor communication

•PRODUCT INFORMATION

Super wide format: 3.15 m  
Rolls of: 60 and 250 lm / printable side inside

Wide format: 1.37 / 1.56 m  
Rolls of: 30 lm / printable side outside

Screenprinting: 3.15 m  
Rolls of: 60 and 250 lm / printable side inside

For special requirements:

Other widths available: 2.78 m - please contact us

- Weight 575 g/m<sup>2</sup>
- Base cloth high tenacity polyester 1100 Dtex
- Coating PVC coating, system LOWICK
- Finish satin inkjet lacquer one side
- Colour white 7325

•PRODUCT CHARACTERISTICS

|                         |                       |                   |
|-------------------------|-----------------------|-------------------|
| - Tensile strength      | 200/210 daN           | NF EN ISO 1421    |
| - Tear strength         | 30/20 daN             | DIN 53363         |
| - Adhesion              | 7 daN/5 cm            | NF EN ISO2411     |
| - Translucency          | 5 %                   | XPT 54 199        |
| - Thickness             | 0.46 mm               |                   |
| - Temperature stability |                       |                   |
| in Celsius              | - 30°C to +70°C       |                   |
| in Fahrenheit           | - 22°F to +158°       |                   |
| - F/R                   | M1                    | PV N°LYC 064240 L |
|                         | B1 - BS - CI2         |                   |
|                         | NFPA 701 – MEA - CSFM |                   |

Average values +/- 10% non contractual

03/2007