

# JET 620

Backlit



M2/B1/BS/CI2

•APPLICATIONS

- One side printing
- Digital printing: solvent / eco-solvent and UV inks
- Screenprinting: solvent and UV inks
  
- Indoor / Outdoor

Billboards / backlit advertising

•PRODUCT INFORMATION

Super wide format: 3.15 m  
Rolls of: 60 and 250 lm / printable side inside

Wide format: not available

Screenprinting: 3.15 m  
Rolls of: 60 and 250 lm / printable side inside

- Weight 600 g/m<sup>2</sup>
- Base cloth high tenacity polyester 1100 Dtex
- Coating PVC coating, system LOWICK
- Finish satin inkjet lacquer one side
- Colour white 7348

•PRODUCT CHARACTERISTICS

- |                         |                       |                |
|-------------------------|-----------------------|----------------|
| - Tensile strength      | 220/210 daN           | NF EN ISO 1421 |
| - Tear strength         | 30/20 daN             | DIN 53363      |
| - Adhesion              | 8 daN/5 cm            | NF EN ISO2411  |
| - Translucency          | 21 %                  | XPT 54 199     |
| - Thickness             | 0.48 mm               |                |
| - Temperature stability |                       |                |
| in Celcius              | - 30°C to +70°C       |                |
| in Farenheit            | - 22°F to +158°       |                |
| - F/R                   | M2                    | PV N° 583 L    |
|                         | B1 - BS - CI2         |                |
|                         | NFPA 701 – MEA - CSFM |                |

Average values +/- 10% non contractual

03/2007