

JET 620



M2/B1/BS

Backlit

• APPLICATIONS

- One side printing
- Digital printing: solvent / eco-solvent and UV inks
- Screenprinting: solvent and UV inks
- Indoor / Outdoor
Billboards / backlit advertising

• PRODUCT INFORMATION

Super wide format: 3.20m
Rolls of: 60 lm / printable side inside

Wide format: not available

Screenprinting: 3.20m
Rolls of: 60 lm / printable side inside

- Weight 570 g/m²
- Base cloth high tenacity polyester 1100 Dtex
- Coating PVC coating, system LOWICK
- Finish satin inkjet lacquer one side
- Colour white 7348

• PRODUCT CHARACTERISTICS

- Tensile strength	220/190 daN	NF EN ISO 1421
- Tear strength	25/20 daN	DIN 53363
- Adhesion	8 daN/5 cm	NF EN ISO2411
- Translucency	20 %	XP T 54 199
- Thickness	0.49 mm	
- Temperature stability		
in Celcius	- 30 °C to +70 °C	
in Farenheit	- 22 °F to +158 °	
- F/R	M2	PV N° LYC-05-0251 L
	B1 - BS - CI2	
	NFPA 701 - MEA - CSFM	

Average values +/- 10% non contractual

Collection 2009
Edition 01/2009