



● APPLICATIONS

- One side printing
- Digital printing : solvent / eco-solvent / UV and Latex inks
- Screenprinting : solvent and UV inks

- Indoor / Outdoor

Billboards / banners / signage / POS / wall covering

● PRODUCT PACKAGING

- **Super Wide format** : 2.24m / 2.50m / 2.78m / 3.20m
Rolls of : 60 lm / printable side outside
- **Wide Format** : 0.76m / 1.06m / 1.10m / 1.37m / 1.52m / 1.62m / 2.24m / 2.50m / 3.20m
Rolls of : 30 lm / printable side outside
- **Screenprinting** : 0.90m / 1.00m / 1.10m
Packaging : 4 rolls of 60 lm / pallet / printable side outside
2.24m / 2.50m / 2.78m / 3.20m
Rolls of 60 lm / printable side outside

● PRODUCT CHARACTERISTICS

Weight	575 g/m ²		
Coating	PVC coating System LOWICK	Base cloth	High tenacity polyester 1100 Dtex
Colour	White 7325	Finish	Satin inkjet lacquer One side
Thickness	0.48 mm	Translucency XP T 54 199	5%
Tensile strength NF EN ISO 1421	210/200 daN	Tear strength DIN 53363	30/20 daN
Temperature Stability	-30°C to +70°C -22°F to + 158°F	Adhesion NF EN ISO 2411	7 daN/5cm
F / R	DIN 75 200 (PV n°LYC-10-1715)		