

LACOPACS

Blackout / 680 g/m²



● APPLICATIONS

- **Both side printing**
- **Digital printing** : solvent / eco-solvent and UV and Latex inks
- **Screenprinting** : solvent and UV inks

- **Indoor / Outdoor**
Signage / banners / POS / indoor communication

- **Advantage** : No curling



● PRODUCT PACKAGING

- **Super Wide format** : 2.78m / 3.10m
Rolls of : 60 lm / printable side outside

- **Wide Format** : 1.37m / 3.10m
Rolls of : 30 lm / printable side outside

- **Screenprinting** : 0.90m / 1.00m / 1.10m
Packaging : 4 rolls of 60 lm / pallet / printable side outside
2.78m / 3.10m
Rolls of 60 lm / printable side outside

● PRODUCT CHARACTERISTICS

Weight	680 g/m ²		
Coating	PVC coating System LOWICK	Base cloth	High tenacity polyester 550 Dtex
Colour	White 7294	Finish	Satin inkjet lacquer One side
Thickness	0.51 mm	Translucency XP T 54 199	0 %
Tensile strength NF EN ISO 1421	150 / 120 daN	Tear strength DIN 53363	15 / 12 daN
Temperature Stability	-30°C to +70°C -22°F to + 158°F	Adhesion NF EN ISO 2411	5 daN/5cm
F / R	M1 (PV N LYC 07-4253 L) B1 / BS		