

LACOPACS

Blackout / 680 g/m²



● APPLICATIONS

- **One side printing**
- **Digital printing:** solvent / eco-solvent and UV and Latex inks
- **Screenprinting:** solvent and UV inks
- **Indoor / Outdoor:** Signage / banners / POS / indoor communication
- **Advantage:** No curling



● PRODUCT PACKAGING

- **Super Wide format:** 2.78m / 3.10m
Rolls of: 60 ml / printable side outside
- **Wide Format:** 1.02m / 1.37m / 3.10m
Rolls of: 25 ml / printable side outside
- **Screenprinting:** 0.90m / 1.00m / 1.10m
Packaging: 4 rolls of 60 ml / pallet / printable side outside
2.78m / 3.10m
Rolls of 60 ml / printable side outside

● PRODUCT CHARACTERISTICS

Weight	680 g/m²		
Coating	PVC coating System LOWICK	Base cloth	High tenacity polyester 550 Dtex
Colour	White 7294	Finish	Satin inkjet lacquer One side
Thickness	0.51 mm	Translucency XP T 54 199	0 %
Tensile strength NF EN ISO 1421	150 / 120 daN	Tear strength DIN 53363	15 / 12 daN
Temperature Stability	-30°C to +70°C -22°F to + 158°F	Adhesion NF EN ISO 2411	6 daN/5cm
F / R	M2 / B1		

